

CABLE PARAMETERS

Module	Group	BASEEFA			FM		
		μF	mH	or $\mu\text{H}/\Omega$	Group	μF	mH
MTL5011B/5018	IIC	2.41	175	983	A+B	2.4	165
	IIB	16.8	680	1333	C	7.2	495
	IIA	75	1000	1333	D	19.2	1320
MTL5012/5015 5017	IIC	2.4	165	825	A+B	2.4	165
	IIB	7.2	495	2475	C	7.2	495
	IIA	19.2	1320	6600	D	19.2	1320
MTL5014	IIC	2.41	170	681	A+B	2.41	170
	IIB	16.8	510	2045	C	16.8	510
	IIA	75	1360	5454	D	75	5454
MTL5021	IIC	0.11	1.30	40	A+B	0.17	1.32
	IIB	0.84	3.90	159	C	0.51	3.96
	IIA	2.97	10.4	328	D	1.36	10.56
MTL5023/5024	IIC	0.17	1.32	37	A+B	0.17	1.32
	IIB	0.51	3.96	111	C	0.51	3.96
	IIA	1.36	10.56	296	D	1.36	10.56
MTL5022	IIB	0.51	3.96	90	C	0.51	3.96
	IIA	1.36	10.56	240	D	1.36	10.56
MTL5025	IIC	0.11	4.3	63	A+B	0.17	4.2
	IIB	0.84	17.72	235	C	0.51	12.6
	IIA	2.97	36.02	497	D	1.36	33.6
MTL5031/5051	Consult MTL						
MTL5032	terminals 2 to 1						
	IIC	2.4	165	825	A+B	2.4	165
	IIB	7.2	495	2475	C	7.2	495
	IIA	19.2	1320	6600	D	19.2	1320
	terminals 4 to 3 and 1						
	IIC	0.13	1.57	55	A+B	0.13	4.2
	IIB	0.39	4.71	165	C	0.39	12.6
	IIA	1.04	12.56	440	D	1.04	33.6
	Terminals 5 to 4 and						
IIC	0.13	4.2	55	A+B	0.13	4.2	
IIB	0.39	12.6	165	C	0.39	12.6	
IIA	1.04	33.6	440	D	1.04	33.6	
MTL5040	IIC	-	-	-	A+B	-	-
	IIB	-	-	-	C	-	-
	IIA	-	-	-	D	-	-
MTL5041/5042/ 5044/5046/ 5061/5043 5045/5049	IIC	0.083	3.05	55	A+B	0.13	4.2
	IIB	0.65	9.15	210	C	0.39	12.6
	IIA	2.15	24.4	444	D	1.04	33.6
MTL5053	IIC	0.165	0.32	31	A+B	-	-
	IIB	1.14	3.00	126	C	-	-
	IIA	4.20	7.00	242	D	-	-
MTL5073/5074	Terminals 1&3 and 4&5						
	IIC	0.26	6.0	164	A+B	0.26	6.0
	IIB	0.78	18.0	492	C	0.78	18.0
	IIA	2.08	48.0	1312	D	2.08	48.0
	Config. Socket						
	IIC	0.6	47	135	A+B	0.60	47
IIB	1.80	141	405	C	1.30	141	
IIA	4.8	376	1080	D	4.8	376	
MTL5081	IIC	100	15	2,972	A+B	-	-
	IIB	1,000	60	11,889	C	-	-
	IIA	1,000	120	23,779	D	-	-
MTL5082	IIC	22.0	48.7	322	TBA	TBA	TBA
	IIB	500	178.4	1,250			
	IIA	1,000	363.7	1,705			
MTL5314	IIC	-	-	-	A+B	-	-
	IIB	-	-	-	C	-	-
	IIA	-	-	-	D	-	-

