

AC230 Series

Premium Series Triaxial Accelerometer, Connector/Cable, 100 mV/g

SECTION I - VIBRATION SENSORS Accelerometers

Must Use J4A or J4C Connectors
Must Use CB105, CB117, CB119 or CB218 Cables

Product Features

Premium Triaxial Sensor
Collect 3 Axes of Data



Actual Product Size Shown



- Premium ±5% Sensitivity
- Reduces Data Collection Time
- 1/4-28 or M6x1 Captive Bolt

AC230-1D

4 Pin Connector

Connector Pin Polarity		Azima DLI Compatible Connector Pin Polarity	
A	Axis Y (+) Signal / Power	A	Axis 3 (+) Signal / Power
B	Axis X (+) Signal / Power	B	Axis 2 (+) Signal / Power
C	Axis Z (+) Signal / Power	C	Axis 1 (+) Signal / Power
D	(-) Common / Grid	D	(-) Common / Grid

CTC multi-conductor cable

Red = Y axis
 Green = X axis
 White = Z axis
 Black = Common

ALIGNMENT GUIDE (PIN)

AC230-2D

Integral Cable

Conductor Polarity		Azima DLI Compatible Conductor Polarity	
Red	Axis Y (+) Signal / Power	Red	Axis 3 (+) Signal / Power
Green	Axis X (+) Signal / Power	Green	Axis 2 (+) Signal / Power
White	Axis Z (+) Signal / Power	White	Axis 1 (+) Signal / Power
Black	(-) Common / Grid	Black	(-) Common / Grid

AC230-3D

Armored Integral Cable

Conductor Polarity		Azima DLI Compatible Conductor Polarity	
Red	Axis Y (+) Signal / Power	Red	Axis 3 (+) Signal / Power
Green	Axis X (+) Signal / Power	Green	Axis 2 (+) Signal / Power
White	Axis Z (+) Signal / Power	White	Axis 1 (+) Signal / Power
Black	(-) Common / Grid	Black	(-) Common / Grid

Specifications	Standard	Metric
Part Number	AC230	M/AC230
Sensitivity (±5%)	100 mV/g	
Frequency Response (±3dB)	36-600,000 CPM	0,6-10000 Hz
Frequency Response (±10%)	60-390,000 CPM	1,0-6500 Hz
Frequency Response (±5%)	480-330,000 CPM	8,0-5500 Hz
Dynamic Range	± 50 g, peak	
Electrical		
Settling Time	<2.5 seconds	
Voltage Source	18-30 VDC	
Constant Current Excitation	2-10 mA	
Spectral Noise @ 10 Hz	27 µg/√Hz	
Spectral Noise @ 100 Hz	6.5 µg/√Hz	
Spectral Noise @ 1000 Hz	2.5 µg/√Hz	
Output Impedance	<100 ohm	
Bias Output Voltage	10-14 VDC	
Case Isolation	>10 ⁸ ohm	

Specifications	Standard	Metric
Environmental		
Temperature Range	-65 to 250°F	-54 to 121°C
Electromagnetic Sensitivity	CE	
Sealing	Welded, Hermetic	
Submersible Depth (AC230-2D/3D)	200 ft.	60 m
Physical		
Sensing Element	PZT Ceramic	
Sensing Structure	Shear Mode	
Weight	7.1 oz	200 grams
Case Material	316L Stainless Steel	
Mounting	1/4-28	
Connector (non-integral)	4 Pin	
Mounting Torque	1 to 2 ft. lbs.	1,4 to 2,7 Nm
Mounting Hardware	1/4-28 Captive Bolt	M6x1 Captive Bolt
Calibration Certificate	CA10	

Ordering Information

Standard	AC230-1D (1/4-28 Captive Bolt)	AC230-2D - / [] - [] (1/4-28 Captive Bolt) (length in feet) (termination)	AC230-3D - / [] / [] - [] (1/4-28 Captive Bolt) (maximum armor length 100 ft.) (cable length in feet) (termination)
Metric	M/AC230-1D (M6x1 Captive Bolt)	M/AC230-2D - / [] - [] (M6x1 Captive Bolt) (length in feet) (termination)	M/AC230-3D - / [] / [] - [] (M6x1 Captive Bolt) (maximum armor length 100 ft.) (cable length in feet) (termination)
		[] M - [] (length in meters) (termination)	[] M / [] M - [] (maximum armor length 30 m) (cable length in meters) (termination)

Cable Termination Options: L Z

Note: CTC multi-conductor cable; Red = Y axis, Green = X axis
 White = Z axis, Black = Common



19 Waterman Ave, Toronto, Ont. M4B1Y2
 Ph#416-445-5500 Fax#416-445-1170
 Toll Free: 1-800-465-1600
 Email:sales@intertechnology.com
 Website:www.intertechnology.com



VIBRATION ANALYSIS HARDWARE