


**HAND
PUMP**



HP-100

- Lever action piston pump with lockable handle
- Dual-flo® handle provides high volume and low volume settings.
- Pumps fluid on both the push and pull strokes for fast delivery.
- Built-in anti-siphon valve
- **For Use with:** Gasoline, diesel fuel, kerosene, medium oil (up to 30W) and hydraulic fluid

ORDERING INFORMATION

Model	Part No.	Nozzle	Certifications
HP-100-NUL	114000-5	Thermoplastic	--
HP-100-UL	114000-10	Metal	 Hose and Nozzle

HP-100 SPECIFICATIONS

Flowrate (GPM / LPM)	Up to 50 Gal/189 Litres per 100 Strokes
Type	Piston
Nozzle	Thermoplastic or Metal
Inlet / Outlet Size	1 in. / 3/4 in.
Tank Fitting	2 in.
Dispensing Hose	8 ft. (2.5 m) x 3/4 in.
Suction Pipe	Telescoping 15 in. to 40 in.
Warranty	2 Year Pump

HP-100-NUL



HP-100-UL



HAND PUMPS

HAND PUMP



HP-90

- Lever action piston pump
- Pumps fluid on both the push and pull strokes for fast delivery
- Built-in anti-siphon valve
- **For Use with:** Gasoline, diesel fuel and kerosene. Light oil (up to 10W) and hydraulic fluid



DP-20

- Lever action diaphragm pump with lockable handle
- Can be used for dirty or contaminated fluids
- **For Use with:** Gasoline, diesel fuel, kerosene, medium oil (up to 30W) and hydraulic fluid

HP-90 SPECIFICATIONS

Flowrate (GPM / LPM)	25 / 95 per 100 Strokes
Type	Piston
Nozzle	Thermoplastic
Inlet / Outlet Size	1 in. / 3/4 in.
Tank Fitting	2 in.
Dispensing Hose	8 ft. (2.5 m) x 3/4 in.
Suction Pipe	Telescoping 15 in. to 40 in.
Warranty	2 Year Pump

DP-20 SPECIFICATIONS

Flowrate (GPM / LPM)	20 / 76 per 100 Strokes
Type	Diaphragm
Nozzle	Thermoplastic
Inlet / Outlet Size	1 in. / 3/4 in.
Tank Fitting	2 in.
Dispensing Hose	8 ft. (2.5 m) x 3/4 in.
Suction Pipe	Telescoping 15 in. to 40 in.
Warranty	2 Year Pump

ORDERING INFORMATION

Model	Part No.	Nozzle	Certifications
HP-90	131000-1	Thermoplastic	--

ORDERING INFORMATION

Model	Part No.	Hose	Certifications
DP-20	138000-01	Buna-N®	--
DP-20-UL	138000-02	U.L. Listed	UL LISTED

HP-90



DP-20 / DP-20-UL



HAND PUMP



RP-10

- Rotary action pump with lockable handle for security
- Built-in anti-siphon valve
- **For Use with:** Gasoline, diesel fuel, kerosene, medium oil (up to 30W) and hydraulic fluid



RP-5


- Basic, rotary action pump
- **For Use with:** Petroleum based fluids having a flash point above 100° F. Diesel fuel and kerosene. Light oil (up to 10W) and hydraulic fluid. **Do not use with gasoline.**



LP-50

- Lever action pump
- Works with drums up to 36 in.
- **For Use with:** Water, Antifreeze, Petroleum Based Products, Mild Detergents, Lubricants and most Ag Chemicals. **Not for use with kerosene, Diesel Fuel, Roundup® Concentrate or Flammable Fluids.**

RP-10 SPECIFICATIONS

Flowrate (GPM / LPM)	10 / 38 per 100 Revolutions
Type	Rotary
Nozzle	Metal
Inlet / Outlet Size	1 in. / 3/4 in.
Tank Fitting	2 in.
Dispensing Hose	8 ft. (2.5 m) x 3/4 in. with Static Wire
Suction Pipe	Telescoping 15 in. to 40 in.
Certifications	
Warranty	2 Year Pump

RP-5 SPECIFICATIONS

Flowrate (GPM / LPM)	8 / 30 per 90 Revolutions
Type	Rotary
Nozzle	Spout
Inlet / Outlet Size	N/A
Tank Fitting	2 in.
Dispensing Hose	N/A
Suction Pipe	Three-Piece Metal
Warranty	90 Days

LP-50 SPECIFICATIONS

Flowrate	Up to 1 Pint per Stroke
Type	Piston
Nozzle	Spout
Inlet / Outlet Size	3/4 in. x 1 in. hose barb
Tank Fitting	2 in.
Dispensing Hose	N/A
Suction Pipe	Telescoping to 36 in.
Warranty	90 Days

ORDERING INFORMATION

Model	Part No.
RP-10-UL	123000-06

ORDERING INFORMATION

Model	Part No.
RP-5	129003-1

ORDERING INFORMATION

Model	Part No.
LP-50	129000-1

RP-10



RP-5



LP-50



HAND PUMPS

HAND PUMP



BP-12

- Lever action piston pump
- Convenient lever handle on a barrel pump
- **For Use with:** Lightweight petroleum products, oils, anti-freeze and kerosene.

CP-5

- Plunger action piston pump
- Very portable and requires no special tools to install. Slips into a five gallon pail.
- **For Use with:** Hydraulic fluids, transmission fluids or motor oils

BP-10

- Basic plunger action pump
- Removable spout for garden hose attachment
- **For Use with:** Petroleum products such as light oil (up to 10W), transmission fluid and hydraulic fluid.

BP-12 SPECIFICATIONS

Flowrate (GPM / LPM)	Up to 1 Pint per Stroke
Type	Piston
Nozzle	Spout
Inlet / Outlet Size	N/A
Tank Fitting	2 in.
Dispensing Hose	N/A
Suction Pipe	Telescoping to 36 in.
Warranty	90 Days

CP-5 SPECIFICATIONS

Flowrate (GPM / LPM)	Up to 8 Ounces per Stroke
Type	Piston
Nozzle	Clear tubing
Inlet / Outlet Size	N/A
Tank Fitting	N/A
Dispensing Hose	N/A
Suction Pipe	N/A
Warranty	90 Days

BP-10 SPECIFICATIONS

Flowrate (GPM / LPM)	Up to 1.5 Pints per Stroke
Type	Piston
Nozzle	Spout
Inlet / Outlet Size	N/A
Tank Fitting	2 in.
Dispensing Hose	N/A
Suction Pipe	Telescoping to 36 in.
Warranty	90 Days

ORDERING INFORMATION

Model	Part No.
BP-12	129010-1

ORDERING INFORMATION

Model	Part No.
CP-5	129002-1
CP-5 (20-PACK)	129002-1M20

ORDERING INFORMATION

Model	Part No.
BP-10	129020-1

BP-12



CP-5



BP-10

