Chemline Plastics vs. "the Competition"

CHEMLINE Plastics Limited

HC Series High Capacity 6" Ball Valves



- Obstructionless flow – most competition offer 4" ball valves with ends increased to 6"
- Selection of body materials, PVC, PP & PVDF
- Bolted-in cartridge body – all parts replaceable
- No dead space around ball, preferred for pure water systems
- Easy to actuate using slotted flat top surface

SR Series Pressure Regulators



- Broader size range – 3/8" to 3" – in all materials, PVC, PP & PVDF
- Larger set range than competition 15–135psi (3/8" to 1-1/2") 15–90 psi (2" to 3")
- Large diameter molded Teflon® control diaphragm for better sensitivity and longer life
- Moulded true union end connections are standard up to 2"– most other brands have FNPT ends
- Unique pressure gauge port on both sides of valve may be used to monitor either upstream or downstream pressures

Variable Area Flow Meters



- Larger size and flow range vs. other brands – up to 2-1/2" size, 220 USGPM capacity
- Wider selection of tube materials including PVC
- Superior chemical resistance vs. low cost acrylic meters
- No float stabilizer rod provides for superior accuracy, better corrosion resistance and lower pressure drops
- Custom flow scales are available next day for specific services
- True union end connections allow for easy removal and cleaning in all sizes
- Optional max/min flow switches and 4–20 mA transmitter

SI Series Gauge Isolators



- Stainless Steel reinforcing bands on end connections eliminate risk of splitting when threading onto tapered NTP connectors
- Better selection of body materials than competition, PVC, PP & PVDF
- Only Chemline offers both process and instrument ports in either 1/4" or 1/2" – any combination available
- Large diameter dished Teflon® diaphragm provides superior sensitivity and longer life

SB Series Back Pressure/ Relief Valves



- Broad size range – 3/8" to 4" – in all materials, PVC, PP & PVDF
- Low overpressures required to fully open
- Large diameter molded Teflon® control diaphragm for better sensitivity and longer life
- Specific models available to handle "dirty" fluids – most competition do not
- Moulded true union end connections are standard up to 2" – most other brands have FNPT ends
- Unique pressure gauge port on both sides of valve may be used to monitor either upstream or downstream pressures

Chemline Plastics maintains a large stock of the above items

CHEMLINE Plastics Limited
55 Guardsman Road
Thornhill, Ontario
Canada, L3T 6L2
Tel: 905-889-7890
info@chemline.com
www.chemline.com

Your Pipeline To Quality Valves, Piping, Flow Meters and Controls