# Industrial Multi-Zone Temperature Testers

**measure and display temperature differential between 1 and 2 probes**

## Model SH66A
**(Three probe)**

- ***NO CONSTANT MONITORING!*** Min/Max memory collects highest & lowest temperatures
- ***SCAN*** feature stores min/max data from all 3 probes
- Detachable #1075 general purpose probe, #2010 air probe and #4010 surface probe
- Battery eliminator jack (#9317 optional power supply)
- Automatic shut-off after approximately 15 minutes with ***override*** option



## Model SH44A (not shown)
**(Dual probe)**

- Detachable #1075 general purpose probe and #4010 surface probe

### SH66A Series and SH44A Series also feature...

- Sealed membrane touchpad that ***protects against spills and dust***
- ***Rugged*** 9.5" x 6.5" x 3.5" (closed) polyethylene storage case
- 9 volt alkaline battery
- Backlight for dark environments

## Model SH66A Only
## Model SH44A Only

- Unit in carrying case, excluding probes

## Model SH66AC
## Model SH44AC

- Celsius prominent
- Includes 7 language instruction booklet (Not available with the SH44AC)

| | |
|---|---|
| **Range:** | -40 to 300°F (-40 to 150°C) |
| **Resolution:** | 0.1°F or °C |
| **Accuracy:** | ± 0.3°F / ± 0.2°C, or ±0.5% of reading, whichever is greater |
| **Ambient Range:** | 0 to 130°F max. (-18 to 54°C) |
| **Ambient Humidity Range:** | Max. RH 90% non-condensing |
| **Display:** | 4 digit LCD 0.5" high |

**Display Indications**

| | |
|---|---|
| **LO:** | Temp is below -40°F (-40°C) or open probe |
| **HI:** | Temp is above 300°F (150°C) or shorted probe |
| **LO-P:** | Battery is discharged |
| **1, 2, or 3:** | Zone being monitored |
| **°F:** | Temperature in Fahrenheit |
| **°C:** | Temperature in Celsius |
| **CL:** | Clear min/max memory (not available on SH44A) |
| **SCAN:** | Multi-channel data collection mode (not available on SH44A) |