

MT-498 21.5" Panel PC (1920 x 1080 / Full HD)

NO. DS200640240109 | EN
2015 | V 01.00.03



MT-498 – 21.5" (1920 x 1080)

R. STAHL's brand new, innovative 4x8 Panel PC SERIES has been designed specifically for the oil and gas industry. Suitable for use in Zone 2 and Zone 22 hazardous areas, these units are ideal for a wide range of applications on both onshore and offshore drilling rigs, e.g. for mud logging, MWD / LWD, rig instrumentation, well stimulation, etc.

The powerful Intel Core i7 processor, the advanced sunlight-readable display with multi-touch technology, and a wide variety of functions make this system a highly innovative human-machine interface.

The 4x8 Panel PC SERIES features the latest trends in networking technology, e.g. dual Ethernet ports, or safe, 802.11a/b/g/n, IS WLAN module. The built-in Bluetooth and camera enable VoIP video conferencing. The Panel PC also comes with RFID reader interface for fast user authentication.

This new series is rugged and IP66-rated, provides outstanding resistance to shock and vibration, and is capable of operating at temperatures ranging from -40 °C to +65 °C [-40 °F to 149 °F].

Explosion protection Certificate / Marking



ATEX directive 94/9/EC

BVS 14 ATEX E 134 X
II 3 (1) G Ex nA nR [ia op is Ga] IIC T4 Gc
II 3 (1) D Ex tc [ia op is Da] IIIC T115°C Dc

IECEX

BVS 14.0116X
Ex nA nR [ia op is Ga] IIC T4 Gc
Ex tc [ia op is Da] IIIC T115°C Dc

Additional certificates:

Russia (TR), Canada (CSA),
Korea (KCC), Brazil (INMETRO)
(pending)

Ambient temperatures

Operation -10 °C to +65 °C [14 °F to 149 °F]
-40 °C to +65 °C [-40 °F to 149 °F] (option)
Storage -20 °C to +70 °C [-4 °F to 158 °F]



Hardware

- Brilliant 21.5" colour and sunlight-readable display with 1920 x 1080 pixels (format 16:9)
- Capacitive multi-touch screen with hardened glass front
- Robust, seawater-proof metal enclosure powder coated with IP66
- Extreme temperature range from -40 °C to +65 °C [-40 °F to 149 °F] (with integrated heating option)
- Powerful processor Intel Core i7® or AMD G-Series T56

Firmware / Software

- Operating system
 - Windows Embedded Standard® 7
 - Windows® 7 Ultimate
 - Driver support for other operating systems (on request)

Front and back side IP66

MT-498 21.5" Panel PC (1920 x 1080 / Full HD)

NO. DS200640240109 | EN
2015 | V 01.00.03



Technical data			
Design	VESA, Yoke or pipe mount, sun shade and mobile options		
Display	55 cm (21.5") TFT colour display 16.777.216 colours Full HD 1920 x 1080 Aspect ratio 16:9		
Backlight	Long life LED technology Service life 70,000 h at +25 °C [77 °F]		
Function keys at display	8 function keys Capacitive touch keys		
External keyboard	Yes (optional), attached keyboard and pointing device (trackball or joystick) (Ex ia) or desktop keyboard 105 keys (Ex ia) and optical desktop mouse (Ex ia)		
Processor / memory	AMD G-Series T56 1.6 GHz 2 cores 4 GB RAM, 60 GB SSD		
Operating system	Windows Embedded Compact 7, Windows 7 Ultimate		
Languages	Multilanguage operating system: en, de, fr, es, it, br, ru, kr		
Interfaces	<table border="0"> <tr> <td> Standard interfaces 2 x Ethernet 10/100/1000Base-TX (Ex nA) or FO 100Base-FX, 100 Mbit (Ex op is), SC connectors 1 x USB (Ex nA) 3 x USB (Ex ia) 1 x Serial interface RS-232 / RS-422 / RS-485 (Ex nA) 1 x Audio line out (Ex nA) (only AMD processor) DVI out (Ex nA) Integrated front camera 5 Megapixel Reader / barcode reader interface (Ex i) </td> <td> Optional interfaces Bluetooth WIFI 2.4 GHz (Ex i) WIFI 5 GHz (Ex i) </td> </tr> </table>	Standard interfaces 2 x Ethernet 10/100/1000Base-TX (Ex nA) or FO 100Base-FX, 100 Mbit (Ex op is), SC connectors 1 x USB (Ex nA) 3 x USB (Ex ia) 1 x Serial interface RS-232 / RS-422 / RS-485 (Ex nA) 1 x Audio line out (Ex nA) (only AMD processor) DVI out (Ex nA) Integrated front camera 5 Megapixel Reader / barcode reader interface (Ex i)	Optional interfaces Bluetooth WIFI 2.4 GHz (Ex i) WIFI 5 GHz (Ex i)
Standard interfaces 2 x Ethernet 10/100/1000Base-TX (Ex nA) or FO 100Base-FX, 100 Mbit (Ex op is), SC connectors 1 x USB (Ex nA) 3 x USB (Ex ia) 1 x Serial interface RS-232 / RS-422 / RS-485 (Ex nA) 1 x Audio line out (Ex nA) (only AMD processor) DVI out (Ex nA) Integrated front camera 5 Megapixel Reader / barcode reader interface (Ex i)	Optional interfaces Bluetooth WIFI 2.4 GHz (Ex i) WIFI 5 GHz (Ex i)		
Dimensions (W x H x D)	553 mm x 458 mm x 141 mm [1.81 ft. x 1.50 ft. x 0.46 ft.]		
Cut-out	No panel mount		
Weight	35 kg [77.16 lbs]		
Power supply	20...30 VDC 100...240 VAC (Um 250 VAC), 50 ... 60 Hz		
Ambient temperatures	Operation: -10 °C to +65 °C [14 °F to 149 °F] -40 °C to +65 °C [-40 °F to 149 °F] (option) Storage: -20 °C to +70 °C [-4 °F to 158 °F]		
Heat dissipation	Via heat pipes and cooling fins		
Relative humidity	>95 % at +65 °C [149 °F] according IEC 60068-2-30		
Vibration resistance	According EN 60068-2-6 and DNV marine certification vibration class A		
Material front	Seawater resistant and coated aluminium, hardened glass		
Material back	Seawater resistant and coated aluminium		
Type of protection	Full protected IP66		

MT-498 21.5" Panel PC (1920 x 1080 / Full HD)

NO. DS200640240109 | EN
2015 | V 01.00.03



Type code field system Panel PC

Description	Code	MT-	4	98	-	3					0	0	0	0	-	B	3		0	0	0	0	0	0	0	0	0
Device series																											
Zone 2, 22	MT-																										
Panel PC	4																										
Display size 55 cm / 21.5" display, 1920 x 1080 pixels	98																										
Ethernet																											
2 x copper Ethernet interface 10/100/1000Base-TX (Ex nA)	2TX																										
2 x optical fibre Ethernet interface 100Base-FX (Ex op is)	2FX																										
1 x copper Ethernet interface 10/100/1000Base-TX (Ex nA) (for WLAN devices)	1TX																										
Processor type																											
AMD G-T56N	2																										
Intel Core i7-3517 UE	3																										
RAM: 4 GB	3																										
Display type																											
TFT display	0																										
Sunlight-readable display	1																										
Data memory																											
16 GB C-Fast for Intel Core i7-3517 UE in combination with WES7	3																										
60 GB for AMD G-T56N in combination with WES7	5																										
80 GB for Intel Core i7-3517 UE in combination with WIN 7 Ultimate	6																										
Touch screen																											
None	0																										
Capacitive multi-touch	3																										
Power supply																											
24 VDC (Ex nA)	0																										
100 – 240 VAC, 50 – 60 Hz (Ex nA)	1																										
Optional interface 1																											
No WLAN, no Bluetooth, no RFID	0																										
WLAN 2.4 GHz, no Bluetooth, no RFID	1																										
WLAN 2.4 GHz and 5 GHz, no Bluetooth, no RFID	2																										
No WLAN, Bluetooth, no RFID	3																										
WLAN 2.4 GHz, Bluetooth, no RFID	4																										
WLAN 2.4 GHz and 5 GHz, Bluetooth, no RFID	5																										
No WLAN, no Bluetooth, RFID	6																										
WLAN 2.4 GHz, no Bluetooth, RFID	7																										
WLAN 2.4 GHz and 5 GHz, no Bluetooth, RFID	8																										
No WLAN, Bluetooth, RFID	9																										
WLAN 2.4 GHz, Bluetooth, RFID	A																										
WLAN 2.4 GHz and 5 GHz, Bluetooth, RFID	B																										
Optional interface 2																											
None	0																										
CAN-Bus (CAN Open) (only for AMD G-T56N)	3																										
Option box: none																											
Front / enclosure design: EXICOM VESA 200	0																										
Operating system																											
None (T56 only)	0																										
Windows 7 Ultimate	3																										
Windows Embedded Standard 7 (WES 7)	4																										
Windows Embedded Standard 7 (WES 7) and WINCC flexible	6																										

MT-498 21.5" Panel PC (1920 x 1080 / Full HD)

NO. DS200640240109 | EN
2015 | V 01.00.03



Description	Code	MT- 4 98 - 3 0 0 0 0 - B 3 0 0 0 0 0 0 0 0
Enclosure type		
Rugged panel design (RP)	B	
Material		
Seawater-proof aluminium (powder-coated)	3	
Mounting option		
VESA 200	0	
VESA 200, handle and feet	4	
Outdoor design		
-10 °C	1	
-40 °C	5	
Keyboard layout (see accessories)	0	
Integrated pointing device (see accessories)	0	
Separated pointing device (see accessories)	0	
Separated reader device (see accessories)	0	
Emergency stop button (see accessories)	0	
Separate power supply: none	0	
Further options 1: none	0	
Further options 2: none	0	

Accessories

Media convertor/ Single Port Fibre Switch 9721/13-11-14	1 port 10/100Base-TX RJ45 and 1 port 100Base-FX, fibre optic multi-mode 50 (62,5) / 125 µm (SC)
Mifare cards Mifare-1K-S50-ISO14443-S-10 Mifare-1K-S50-ISO14443-S-100	10 Mifare Proximity access cards 1K S50 - ISO 14443, Front Packaging: Vinyl glossy white 100 Mifare cards, as before