60 Series - Fixed Insertion

DIFFERENTIAL pH or ORP SENSOR

Standard Features

- Accurate differential measurement
- Eliminates ground loop interference
- Built-in pre amplifier
- Transmits up to 3000 ft (900 m)
- Replaceable salt bridge
- 15 ft (5 m) cable
- Flow thru or submersible
- 30-month warranty

Great Lakes Replacement Sensors

Replace any of the following GLI 1-1/2" sensors:

6028P0	2028P0
6058P0	2058P0
6058PI	6051PO

____ - ____ - ____ (____)(____)

Application

pH		**P**
ORP		**R**

Electronics

Standard 5 wire sensor		**60C**
Two wire transmitter, 4-20mA output built-in		**65C**

Body Type

1-1/2" NPT threaded ends, GLI LCP replacement probe		**8**
GLI 605IP0 replacement		**4**
Fixed insertion with sanitary 2-1/2" tri-clover fitting		**S**

Enhanced Performance Options (add only if required)

Antimony electrode, used in hydrofloric acid (pH sensors only)		**A**
Hardened glass electrode		**H**
Flat faced glass electrode (S body type only)		**F**
Gold electrodes for ORP sensors only (platinum is standard)		**G**

Extended Cable Length

Specify cable length [XXX=#ft example-050 = 50 ft]		**XXX**

MOUNTING HARDWARE

STC60L	Submersion hardware	
C35-17	Salt bridge kit with ceramic outer junction (3 pack)	
C35-17-K	Salt bridge kit with kynar outer junction (3 pack)	
C35-170	Graphite salt bridge kit (3 pack)	
AM60-9765	Salt bridge kit with ceramic outer junction for -8 body type probes (3 pack)	
AM60-9765-K	Salt bridge kit with kynar outer junction for -8 body type probes (3 pack)	
JB1	Junction box with integrated terminal strip	
C42-5P-XXX	Interconnect extension cable, 5 wire [XXX=#ft example-050 = 50 ft] price/ft	
C42-1-XXX	Interconnect extension cable, 2 wire [XXX=#ft example-050 = 50 ft] price/ft	
PROTECTOR-3	Electrode protector for -8 body type	
AM-MH538N9A	Union Tee with adaptor for -8 body type, including JB1	