Features

1/2", 3/4" & 1" Ports

For application and feature/ benefit information for the combination units on this page, refer to individual component pages:

Filters - page 47
Regulators - page 48
Lubricators - page 49



28368


Performance Specifications

Max. Inlet Pressure:	200 PSIG (13.8 bar)
Operating Temperature Range:	0° to 125° F (-18° to 52° C)
Filter Element:	40 Micron
Bowl:	Polycarbonate w/ Bowl Guard
Pressure Range in Regulator:	5 to 125 PSI (.4 to 8.6 bar)
Gauge:	0 to 160 PSI

Ordering

PORT SIZE NPT	MODEL	WEIGHT LBS. (kg)	COMPONENTS FILTER	REGULATOR	LUBRICATOR	GAUGE	PIPE NIPPLE
Select the basic model number which represents the port size desired. If other options are desired, order each component separately.							
1/2"	**28343**	10.16 (4.61)	25341-020	27344-000	26341-020	100067	Y27-54-C
3/4"	**28353**	10.12 (4.59)	25351-020	27354-000	26351-020	100067	Y27-55-C
1"	**28363**	9.37 (4.25)	25361-020	27364-000	26361-020	100067	Y27-56-C

GRAPHIC SYMBOL



NOTE: Shipped unassembled. For assembled unit, change the last digit from 3 to 8. Example: 28358.

Performance Specifications

Filter-Regulator

Max. Inlet Pressure:	200 PSIG (13.8 bar)
Operating Temperature Range:	0° to 125° F (-18° to 52° C)
Filter Element:	40 Micron
Bowls:	Polycarbonate w/ Bowl Guard
Pressure Range in Regulator:	5 to 125 PSI (.4 to 8.6 bar)
Gauge:	0 to 160 PSI




28369

Ordering

PORT SIZE NPT	MODEL	GAUGE PORT	WEIGHT LBS. (kg.)	COMPONENTS FILTER	REGULATOR	GAUGE	PIPE NIPPLE
Select the basic model number which represents the port size desired. If other options are desired, order each component separately.							
1/2"	**28344**	1/4"	7.11 (3.22)	25341-020	27344-000	100067	Y27-54-C
3/4"	**28354**	1/4"	7.06 (3.20)	25351-020	27354-000	100067	Y27-55-C
1"	**28364**	1/4"	6.46 (2.93)	25361-020	27364-000	100067	Y27-56-C

GRAPHIC SYMBOL



NOTE: Shipped unassembled. For assembled unit, change the last digit from 4 to 9. Example: 28349