Features

1/2", 3/4" & 1" Ports

Extra rugged Heavy-Duty Series lubricators deliver the reliable lubrication needed for long service life of air line system and equipment. Units are convertible from drop-type to fog-type by rotating sight dome 180 degrees. For best results, lubricator should be located as close as possible to equipment being lubricated.

- Zinc die-cast bodies are corrosion-resistant.
- Tie-rod construction simplifies unit disassembly for quick and easy servicing.
- Two separate fill plugs allow unit to be filled from front or back. Lubricators can be filled under pressure. A quick-fill adapter is available for fast, easy filling.
- Polycarbonate bowl allows visual monitoring. Metallic bowl available for applications involving the use of harsh chemicals. Standard bowl guard protects polycarbonate bowl.



26361-020




26361-220 with tamper Resistant Cap

Performance Specifications

Max. Inlet Pressure:	250 PSIG (17 bar) Metal 200 PSIG (13.8 bar) Polycarbonate	**Body:**	Zinc Die Cast
		Bowls:	Polycarbonate or Steel
		Bowl Guards:	Steel With E-Coat Finish
Oper. Temp. Range:	Polycarbonate bowl - 0° to 125° F (-18° to 52° C) Metal Bowl - 0° to 200° F (-18° to 93° C)	**Sight Glass:**	Polyimide Nyloniz
		Seals:	Buna-N
Oil Capacity:	10 oz. (295 ml)		
Weight:	1/2" = 2.98 lbs. (1.35 kg), 3/4" = 2.83 lbs. (1.28 kg) 1" = 2.70 lbs. (1.22 kg)		
***Flow:**	1/2" = 65 SCFM (31 dm^3/s), 3/4" = 75 SCFM (35 dm^3/s) 1" = 75 SCFM (35 dm^3/s)		

* Flow is at 90 PSIG (6.2 bar) inlet and 5 PSIG (0.4 bar) pressure drop.

GRAPHIC SYMBOL



Manual Drain


Ordering


Select the basic model number which represents the port size desired. From table below, select the number representing lubricator options required.

PORT SIZE	BASIC MODEL
1/2"	26341- X X X
3/4"	26351- X X X
1"	26361- X X X

Shaded area = Best-Selling Models

Adjustment	Bowl Option	Fill Option
0 = Standard Knob	**2** = Polycarbonate w/ guard #29397	**0** = Standard
1 = 1/8" Allen Wrench	**1** = Metal Bowl #29967	**1** = Quick Fill Adapter #29235
2 = Tamper Resistant		





Accessories

Lubricator

MODEL	DESCRIPTION
104069	Polycarbonate Bowl
29967	Metal Bowl
29397	Bowl Guard
29235	Quick-Fill Adapter

MODEL	DESCRIPTION
29665	ARO Lubricating Oil (1 Quart). See pg. 71.
104023	Service Kit
Y57-1	Twist Drain



29235



29967