Over-Run Controls

Model Number	Description	Pumps Used With	Air Inlet NPT	Air Outlet NPT	Pressure Range PSI (bar)
635040	**ARO-STOP® Valve** Shuts off air to the pump when material container is empty or line is broken. Quick set and reset feature.	"N" Series, air motor pumps only	1/4 (F)	1/4 (M)	20-175 (1.4-12)
23644-400	**ARO-STOP® Valve** Shuts off air to the pump when material container is empty or line is broken. Quick set and reset feature.	4¼" & 6" air motor pumps	1/2 (F)	1/2 (M)	20-175 (1.4-12)
635043	**ARO-STOP® Valve** Shuts off air to the pump when material container is empty or line is broken. Quick set and reset feature.	8', 10" & 12" air motor pumps only	3/4 (F)	3/4 (M)	20-175 (1.4-12)



635040

Air Motor Muffler

Model Number	Description	Pump Used With	Air Inlet NPT	Size Inches X Inches PSI (bar)
91790	**Air Motor Muffler** Reduces air exhaust noise level to acceptable OSHA standards.	4¼" & 6" air motor pumps	1-1/4 (M)	3-1/2 x 11-3/16 (89 x 284)
92460	**Air Motor Muffler** Reduces air exhaust noise level to acceptable OSHA standards.	8" air motor, pumps	1-1/4 (M)	5-5/8 x 15-3/8 (143 x 391)
66718	**Air Motor Muffler** Reduces air exhaust noise level to acceptable OSHA standards.	10" & 12" air motor, pumps	Bolted-on	9 x 20 (229 x 508)



91790 92460 66718

Wet Sol "Plus"

Model Number	Description	Used With
66333-B	**Wet Sol - One Quart Container** Designed to prolong packing life by keeping the piston rod and packings wetted. Also reduces the possibility of material hardening on the piston rod.	All pumps with wet cups.
66334-B	**Wet Sol -** One Gallon Container	



66334-B

Get in the ZONE